

TOPSWING

The blood mixing and weighing device of the next generation - for mobile and stationary use

- Modular set-up
- Infrared remote control
- Large VGA display
- Integrated carrying facility
- Ethernet connection
- Innovative mixing motion
- Data transfer via USB stick
- DECT radio technology



TOPSWING PRO

TOPSWING PRO offers all advantages of comfortable data transfer. Combined with TRANSComm it is your optimal solution for collection monitoring.

TOPSWING CL

Your economic alternative. Except for data management functions via DECT radio technology, all crucial quality features are available.

TOPSWING

Ordering Information and Technical Data

Description	Order No.
TOPSWING PRO Blood mixing and weighing device	97.8700.400
TOPSWING CL Blood mixing and weighing device	97.8700.402

Accessories TOPSWING PRO

Description	Order No.
DECT radio module - base station Including data cable	97.8700.460
DECT radio module - base station USB Including data cable	97.8700.461

Accessories TOPSWING CL and TOPSWING PRO

Description	Order No.
TS-Power Charger Simultaneous loading of up to 12 TS-Power-Packs	97.8700.420
TS-Power-Pack 12V, 4500mAh; mobile power supply unit with intelligent charge controller	97.8700.422
Module TS-Power-Pack Module shell for an exchangeable battery incl. drawer	97.8700.430
Modul TS-Seal Module shell including drawer with integrated welding tongs	97.8700.431
Module TS-Transport For the safe transport and storage of TOPSWING; stackable	97.8700.432
Modul TS-Level Enables height setting of TOPSWING during the donation	97.8700.433
Scanner TOUCH 65 PRO Impact-resistant, nonwearing barcode scanner	97.8700.440
USB-Stick Mobile data carrier 1 gigabyte	97.8700.445
TS-Script-Manager Consisting of: · TS-script program to generate a TOPSWING configuration file Including installation CD for Windows XP	97.8700.450
TS-Software licence	97.8700.451
TS-TRANSComm II For the transfer of collection data to the central computer incl. collection monitoring Including installation CD for Windows XP	97.8700.452
Customised Software Customisation of the TOPSWING operating system according to your needs	97.8700.453
RS 232 interface module Communication with up to 16 TOPSWING devices via a serial interface Only required for cable network	97.8700.465
TS-Data cable RS 232 3 m Connection between TOPSWING and host computer	97.8700.466
TS-Data cable RJ45 3 m Connection between TOPSWING and Ethernet network	97.8700.467
TS-Remote control Infrared remote control for the comfortable operation of TOPSWING	97.8700.470

Technical Data

Dimensions (W x H x D): 185 mm x 265 mm x 490 mm
Weighing accuracy: +/- 1%

Voltage: 90 - 264 V; 47 - 63 Hz

Distributed by:

SARSTEDT AG & Co.
P.O. Box 12 20
D-51582 Nümbrecht
Phone +49 2293 3050
Fax +49 2293 305-122
info@sarstedt.com
www.sarstedt.com

